

3-1/2" Thermal Fixed Windows for FEMA 361 / ICC 500 application

Product Information



GLAZING

The glazing options for FEAM 361 / ICC 500 Storm Shelters are limited to the tested configurations. While the exterior insulated (I.G.) lite could be replaced with a 1" monolithic multi layered laminate (3 or 5 ply Glass Clad Polycarbonate) unit, this ballistic configuration has not been tested and is therefore not listed. See the quick reference chart below for all glazing options.

Glazing Thickness		1/8"	3/16"	1/4"	7/16"	1/2"	9/16"	7/8"	1"	1-3/8"	1-3/4"	2"	2-3/8"	-	-
Monolithic		-	-	-	-	-	-	-	-	-	-	-	-	-	-
Insulated		-	-	-	-	-	-	-	-	-	-	-	-	-	-
Dual Glazed	Exterior	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Interior	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Triple Glazed	Exterior	-	-	-	-	-	-		X	-	-	-	-	-	-
	Interior	-	-	-	-	X	-	-	-	-	-	-	-	-	-

Winco has different gaskets and glazing methods that can accommodate odd thicknesses of glass. If you do not see what you are looking for within this chart please contact your local representative for information regarding your specific project needs.

WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

© WINCO WINDOW COMPANY, INC. 2016