

# 3325 Series 3-1/4" Thermal Casement & Projected Windows

## Product Information



WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

### PERFORMANCE

The Series 3325 window is a thermally broken mainframe and sash that exceeds the performance specification criteria as required by ANSI/AAMA for AW (Architectural Grade) windows.

Project Out - Awning			Casement		
AAMA Rating	AW-80		AAMA Rating	AW-80	
Air Infiltration	0.02 CFM/ft <sup>2</sup>		Air Infiltration	0.02 CFM/ft <sup>2</sup>	
Water	Over 12 psf		Water	Over 12 psf	
Structural	120 psf		Structural	120 psf	
CRF (AAMA 1503)	63		CRF (AAMA 1503)	63	
Center of Glass U-Value	Window U-Factor <sup>3</sup>		Center of Glass U-Value	Window U-Factor <sup>3</sup>	
BTU/Ft <sup>2</sup> x F° x Hr	59" x 24" <sup>2</sup>	60" x 36" <sup>1</sup>	BTU/Ft <sup>2</sup> x F° x Hr	24" x 59" <sup>2</sup>	36" x 60" <sup>1</sup>
0.20	0.42	0.36	0.20	0.42	0.36
0.24	0.45	0.40	0.24	0.45	0.40
0.29	0.49	0.44	0.29	0.49	0.44
0.34	0.52	0.48	0.34	0.52	0.48
0.47	0.63	0.59	0.47	0.63	0.59

This Information is based on current product design, sealed dual glazing, warm edge spacers and testing standards.

Please contact WINCO for project specific information

<sup>1</sup> AAMA 101 Test Size

<sup>2</sup> NFRC Gateway Test Size

<sup>3</sup> Based on NFRC 100

© WINCO WINDOW COMPANY, INC. 2016