

3-1/2" Thermal Fixed Windows for FEMA 361 / ICC 500 application

Product Information



WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

PERFORMANCE

This application is a configuration of the 3350 Series for use in FEMA 361 / ICC 500 shelters. The Series 3350 window is a thermally broken mainframe and sash that exceeds the performance specification criteria as required by ANSI/AAMA for AW (Architectural Grade) windows.

Fixed		
AAMA Rating	150 psf Design Pressure	
Air Infiltration	0.03 CFM/ft ²	
Water	Over 12 psf	
Structural	300 psf	
CRF (AAMA 1503)	63	
Center of Glass U-Value	Window U-Factor ³	
BTU/Ft ² x F° x Hr	47" x 59" ²	60" x 99" ¹
0.20	0.34	0.30
0.24	0.37	0.33
0.29	0.41	0.37
0.34	0.45	0.41
0.47	0.55	0.52

This Information is based on current product design, sealed dual glazing, warm edge spacers and testing standards.

Please contact WINCO for project specific information

¹ AAMA 101 Test Size

² NFRC Gateway Test Size

³ Based on NFRC 100

© WINCO WINDOW COMPANY, INC. 2016