

### HARDWARE

All exposed sweep lock hardware and keepers are solid white bronze alloy with US25D brushed finish. All exposed springloaded snap lock hardware is manufactured from extruded aluminum matching the window frame finish.

| Window Type       | Spring Lock at Jamb | Spring Lock at Head | Spring Lock at Sill | Stainless Steel Wheel w/ SS Bearing | Nylon Wheel w/ Steel Bearing | Stainless Steel Track Cover | Sweep Lock | Access Control Sweep Lock | Class 5 Sash Balance (Ultralift) | Limit Stop (non removable, Extruded) | Limit Stop (Key- Release) |  |  |  |
|-------------------|---------------------|---------------------|---------------------|-------------------------------------|------------------------------|-----------------------------|------------|---------------------------|----------------------------------|--------------------------------------|---------------------------|--|--|--|
| Horizontal Slider | X                   | -                   | -                   | O                                   | X                            | O                           | X          | O                         | -                                | O                                    | -                         |  |  |  |

X = Standard Hardware  
O = Optional Hardware

WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

### SCREENS

**FRAME** - frames are fabricated from 6063-T6 extruded aluminum alloy and temper. All screen frames are miter cut and corner keyed. The corners are mechanically crimped together for durability. The screen frame is finished to match the window frame.

**MESH** - Standard .011 aluminum screen wire mesh is produced from 5154 alloy with 18x16 pattern in Charcoal or Aluminum color. All mesh is applied to the screen frame with a roller spline making for easy and quick replacements. Optional fiberglass or .009 stainless steel mesh is available as an option.

© WINCO WINDOW COMPANY, INC. 2021