

NC-82 Series 3-1/4" Thermal Terrace Doors

Product Information



WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

GLAZING

The windows can be interior or exterior glazed with .055 thick extruded aluminum glazing beads accommodating thicknesses of 5/8" and 1". For actual details refer to the glazing section in the back of the NC-82 section for optional glazing and blind details.

Glazing Thickness	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	9/16"	5/8"	3/4"	7/8"	1"	1-1/4"	1-3/8"	1-1/2"
Monolithic	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Insulated	-	-	-	-	-	-	-	X	-	X	X	-	-	-
Dual Glazed	Exterior	-	-	-	-	-	-	-	-	-	-	-	-	-
	Interior	-	-	-	-	-	-	-	-	-	-	-	-	-
Triple Glazed	Exterior	-	-	-	-	-	-	-	-	-	-	-	-	-
	Interior	-	-	-	-	-	-	-	-	-	-	-	-	-

Winco has different gaskets and glazing methods that can accommodate odd thicknesses of glass. If you do not see what you are looking for within this chart please contact your local representative for information regarding your specific project needs

HARDWARE

All exposed locking hardware is aluminum. All multi point locking hardware is stainless steel conforming to AAMA 904.1. 2 knuckle butt hinges are fabricated of 6063-T6 aluminum with nylon bushings and an adjustable stainless steel hinge pin.

	2 Knuckle Butt Hinge	Paris Style Handle	Multiple Locking Points	Keyed Lock Outside	Thumb Turn Lock Outside	Keyed Lock Inside	Thumb Turn Lock Inside							
Door Type	X	X	X	X	O	O	X
Single Inswing	X	X	X	X	O	O	X							
Single Outswing	X	X	X	X	O	O	X							
Double Inswing	X	X	X	X	O	O	X							
Double Outswing	X	X	X	X	O	O	X							
NC-82 Sidelite	-	-	-	-	-	-	-							
NC-82 Transom	-	-	-	-	-	-	-							

X = Standard Hardware
O = Optional Hardware

© WINCO WINDOW COMPANY, INC. 2021