

3600 Series 3-1/4" Thermal Fixed & Horizontal Sliding Windows

Product Information



WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

PERFORMANCE

The Series 3600 window is a thermally broken mainframe and sash that exceeds the performance specification criteria as required by ANSI/AAMA for AW (Architectural Grade) windows.

| Fixed | | | Single Slider | | |
|-------------------------------|------------------------------|------------------------|-------------------------------|------------------------------|------------------------|
| AAMA Rating | AW-80 | | AAMA Rating | AW-50 | |
| Air Infiltration | 0.0 CFM/ft ² | | Air Infiltration | 0.24 CFM/ft ² | |
| Water | Over 12 psf | | Water | Over 10 psf | |
| Structural | 120 psf | | Structural | 75 psf | |
| CRF (AAMA 1503) | No Test | | CRF (AAMA 1503) | No Test | |
| Center of Glass U-Value | Window U-Factor ³ | | Center of Glass U-Value | Window U-Factor ³ | |
| BTU/Ft ² x F° x Hr | 47" x 59" ² | 60" x 99" ¹ | BTU/Ft ² x F° x Hr | 47" x 59" ² | 99" x 79" ¹ |
| 0.20 | 0.34 ⁴ | 0.29 ⁴ | 0.20 | 0.44 | 0.34 |
| 0.24 | 0.37 ⁴ | 0.33 ⁴ | 0.24 | 0.46 | 0.37 |
| 0.29 | 0.41 ⁴ | 0.37 ⁴ | 0.29 | 0.50 | 0.41 |
| 0.34 | 0.45 ⁴ | 0.41 ⁴ | 0.34 | 0.53 | 0.45 |
| 0.47 | 0.55 ⁴ | 0.52 ⁴ | 0.47 | 0.62 | 0.56 |

This Information is based on current product design, sealed dual glazing, warm edge spacers and testing standards.

Please contact WINCO for project specific information

¹ AAMA 101 Test Size

² NFRC Gateway Test Size

³ Based on NFRC 100

⁴ Estimated performance

© WINCO WINDOW COMPANY, INC. 2021