



# Customizations to Meet Massachusetts New Energy Codes

The WINCO 8325 window series can be customized to maximize energy performance to meet Massachusetts new energy codes. This factory-glazed window system has an overall depth of 3-1/4 inches and is engineered for structural integrity, thermal efficiency, and long-lasting durability. **Some fixed window configurations can achieve U-Values as low as 0.16 (Btu/Hr-Ft<sup>2</sup>-°F).**

The innovative 8325 design significantly warms interior framing temperatures compared to traditional window systems, improving occupant comfort and condensation resistance, especially in cold climates.

## Customizations & Benefits

- Vertical and horizontal stacking members
- Fully mitered overlap sash configuration with fully sealed corners and dual weather-stripping
- Various glazing thicknesses available
- Optional aluminum extruded screens
- Dual glazing with optional integral blinds providing dynamic light control
- Accessory line of receptors, mullions, panning and trim for a customized look



### Performance Data\*

Type	Air (CFM/FT <sup>2</sup> @ 6.24 PSF)	Water (PSF)	Structural (PSF)	U-Value (Btu/Hr-Ft <sup>2</sup> -°F)	STC
Fixed AW Grade AP-AW100	0.0	12 (Higher levels may be available upon request)	+/- 150	0.16*	Contact your local Rep
Projected AW Grade AP-AW100	Less than 0.01	12 (Higher levels may be available upon request)	+/- 150	0.32*	

\*U-Value, CRF, Water and AW ratings are based on a particular type of glazing and window configuration being used. They are provided for comparison purposes only. They are based on products of standard configuration, tested in accordance with NFRC/FGIA/AAMA specifications, in a laboratory environment under optimum conditions. Performance values will vary according to project specifications, installation, size, configuration, hardware, glass, etc. Any required field testing should be done in accordance with the project specifications and FGIA/AAMA field testing protocol, not this data.

